

## European product sheet

PERFORMANCES	
Brand	H.Koenig
Reference	<b>KOL7012</b>
Refrigerating power (kW)	3,5 kw
Heating power (kW)	2.8 kw
Refrigerating power (BTU)	12 000 BTU
Cold power consumption	Cooling = 1350 w
	Heating = 1400 w
Max input power supply	1700w / 8.1A
Global Warning Potential	2088
Coefficient of performance COP Hot	2.5
Energy Efficiency Ratio Cold	2.6
Electricity power HOT	1.4 KWH/60mn
Electricity power COLD	1.4 KWH/60mn
Cold energy label	A
Cold for parts between	Up to 35m <sup>2</sup>
max. pressure input power supply	1.2 / 2.5 MPa
SPECIFICATIONS	
Max. sound power level	63db
Maximum airflow rate	430m <sup>3</sup> /h
Refrigerating gas	R410a / 560g
Climatic class	Class I
FEATURES	
Ventilation	yes
Dehumidication	yes
Cooling	yes
Heating	yes
Remote control	yes
Sleep comfort	yes
Timer	yes
Fan speeds	3
Opening	automatic
Oscillation	yes
FILTER	
Washable pre-filter	yes
TECHNICAL DETAILS	
Voltage / Frequency	AC 220-240V ,50Hz
Power cable length	1.90m
Carrying handles	yes
Included accessories	LCD remote control, exhaust hose, air exhaust tube
Product sheet according to the EU REGULATION N. 106	